

CHINA

DELLENT

CE ISO

DE-DD44

30 DAYS

USD3000-4000

PLASTIC WRAP

500 PCS PER MONTH

Commercial Deutz Diesel Generator 40kVA BFM3T Engine Diesel Generator 50HZ 32kW

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1*20GP CONTAINER
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T, Western Union
- Supply Ability:



Product Specification

- Name:
- Cooling System:
- Frequency:
- Insulation Class:
- Noise Level:
- Controller:
- Phase:
- Power:
- Protection Grade:
- Prime Power:
- Standby Power:
- Highlight:

- Commercial Deutz Diesel Generator
- Water Cooling 50HZ
- Н
- - : ≤75dB(A)
 - Smartgen/Deepsea/ComAp
 - Three Phase
 - Diesel Generator
 - IP23
 - 32kW/40kVA
 - 35.2kW/44kVA
 - Deutz Diesel Generator 40kVA, Commercial Deutz Diesel Generator, Engine Diesel Generator 50HZ

Our Product Introduction

Product Description

High	
. ng n	Commercial Deutz 40kVA Generator, BFM3T Engine Diesel Generator,
Light:	CE Deutz 40kva Generator

.PRODUCT DESCRIPTION

CE Commercial 32kW Deutz 40kVA GeneratorBFM3T Engine Diesel Generator

Product Introduce: Deutz engine diesel generator we have all series from rated 20kva to 750kva.

Application fields:

Diesel generator are used in any situation where a reliable backup power source is necessary to maintain continuity of operations. For example: Healthcare,Data Centers,Telecommunications,Construction,Manufacturing,Oil and Gas,Military,Residential electricity.

Advantage of our Deutz diesel generator :

Deutz diesel generator have a sturdy housing Longer lifespan Lower maintenance costs Lower noise level Faster delivery time Better team service Higher level technical support.



Product parameters

Product parameters:	
Model	DE-DD44
Rated output (KW/KVA)	32kw
Rated voltage (V)	230/400V
Rated current(A)	57.8A
Rated frequency	50Hz
Power factor	0.8 lagging
Noise level dB(a)	70/1m
Excitation	Stamford Brushless self-excitation
Phase Number and connection	3-phase 4-wire system
Diesel Engine	UK,Germany diesel engine,4 stroke,water cooled
Alternator model	Stamford brushless self-excited, IP23,Class H.
Rated Power (kw/1500rpm)	32kw
Fuel consumption (g/kw*h)	<238
Cylinder number	4 cylinders
Displacement (L)	3.3
Cooling system	Water cooling
	Altitude≤1000M, Cooling air temperature



