



## Three Phase 50HZ 24kW Deutz 30 Kva Generator BFM3 G2 Engine Diesel Generator

Our Product Introduction

### Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE ISO
- Model Number: DE-DD33
- Minimum Order Quantity: 1\*20GP CONTAINER
- Price: USD3000-4000
- Packaging Details: PLASTIC WRAP
- Delivery Time: 30 DAYS
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 500 PCS PER MONTH



### Product Specification

- Name: Deutz 30 Kva Generator
- Controller: Smartgen/Deepsea/ComAp
- Cooling System: Water Cooling
- Frequency: 50HZ
- Insulation Class: H
- Noise Level: ≤75dB(A)
- Phase: Three Phase
- Power: Diesel Generator
- Protection Grade: IP23
- Prime Power: 24kW/30kVA
- Standby Power: 26.4kW/33kVA
- Highlight: **Three Phase Deutz 30 Kva Generator, Diesel Generator Deutz 30 Kva Generator, G2 Engine Diesel Generator**

for more products please visit us on [dellentpower.com](http://dellentpower.com)

## Product Description

High **Commercial Deutz 30kVA Generator , BFM3 G2 Engine Diesel Generator ,**  
 Light: **CE Deutz 30kva Generator**

### . PRODUCT DESCRIPTION

CE Commercial 24kW Deutz 30kVA Generator BFM3C Engine Diesel Generator

#### Product Introduce:

Deutz engine diesel generator we have all series from rated 20kva to 750kva.

#### Application fields:

Diesel generator are used in any situation where a reliable backup power source is necessary to maintain continuity of operations.

For example:

Healthcare,Data Centers,Telecommunications,Construction,Manufacturing,Oil and Gas,Military,Residential electricity.

#### Advantage of our Deutz diesel generator :

Deutz diesel generator have a sturdy housing

Longer lifespan

Lower maintenance costs

Lower noise level

Faster delivery time

Better team service

Higher level technical support.



#### Product parameters:

##### Specification of 50kVA Deutz Diesel Generator Set:

Model		DE-DD33
Prime Power	kVA	24
	kW	30
Standby Power	kVA	33
	kW	26.4
Frequency	Hz	50
Output Voltage	V	240

##### Specification of Deutz Alternator:

Engine Model		BFM3 G2
No. of Cylinder		4 Cylinder in line
Bore	mm	98
Stroke	mm	105

Displacement	L	3.168
Cooling Fan Air Flow	m3/min	78.66666667
Compress Air Flow	m3/min	3.333333333
Exhaust Gas Flow	m3/min	6.583333333
Exhaust Gas Temperature		530
Lubrication Oil Capacity	L	7.5
Cooling Water Capacity	L	4.8
Starting Voltage	V	12
Engine Max.Output Power	kW	29

**Specification of Control Panel:**

Controller Brand	Smartgen
Breaker Brand	Delixi
Breaker Capacity (A)	100
Emergency Stop Button	Supply
Automatic Mains Fail (AMF)	Supply
Fuel Level	Supply
Automatic Transfer Switch	ATS as optional part

The control panel supply the full protection with alarm and shutdown of the diesel generator include Start-up fault (generator set shutdown), High coolant temperature (alarm and generator set shutdown), Low oil pressure (alarm and generator set shutdown), Low fuel level (alarm), Low cooling fluid level alarm (as optional), Overload (alarm and generator set shutdown), Battery voltage high (alarm).

Optional controller: Each model of Deepsea, Smartgen, ComAp brand controller.

**. Why Choose Us:**

**D**edicated

We are DEDICATED to meet Customers' need.

**E**nthusiasm

We respond to our Customers' ENTHUSIASM

**L**oyalty

We cherish our Customers' LOYALTY

**L**uxury

We aim to establish our own LUXURY brand

**E**fficient

We offer our EFFICIENT service

**N**ewest

We adopt NEWEST technologies for products

**T**rust

We strive for winning the TRUST from Customers

**. QUALIFICATION CENTIFICATE:**



**. FACTORY INTERIOR:**



**Features:**

**Deutz diesel generator with 24 Volt electric starter ensures easy starting**  
**Complete gen-set with low oil pressure shut down the system**  
**Low fuel cut-out protection**

**If you need Deutz generator with other models technical data, kindly contact us for catalogues!**



**Fuan Dellent Electric & Machinery Co., Ltd.**

+8613706938606    jennifer@dellent.com    dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY,NINGDECIY,FUJIAN.CHINA