



1500RPM / 1800RPM Diesel Generator Ricardo Genset CE Certified

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE/ISO9001
- Model Number: DE-W22~W74
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: 1800RPM Diesel Generator
- Engine Brand: Ricardo
- Cooling Method: Water-Cooling System
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Warranty: 12 Months/1000 Hours
- Highlight: **1800RPM Diesel Generator, 1500RPM Diesel Generator, Ricardo Genset**

for more products please visit us on dellentpower.com

CE Ricardos Diesel Generator about 50kW.

. PRODUCT

Our Product Introduction

for more products please visit us on dellentpower.com

50 Hz		60 Hz		TECHNICAL DATA		RICARDO WATER-COOLED Series Diesel Generator Sets					
Generator Performance				Engine model		Engine Performance				Dimension(L*W*H)	
Generator Model	Prime Power kW	Standby Power kW	Engine model	Speed rpm	Prime power kW	Fuel Cons. (100% Load) L/h	Cylinder Bore*Stroke Qty. mm	Displace-ment L	Open Type mm	Silent Type mm	
DE-W22	16	20	4YT23-20D	1500	20	<240	4 88*95	2.31	130x78x96	220x93x123	
DE-W27	20	25	N4100DS-30	1500	30	<225	4 100*115	3.61	130x78x96	220x93x123	
DE-W33	24	30	N4100DS-30	1500	30	<225	4 100*115	3.61	130x78x96	220x93x123	
DE-W41	30	38	N4105DS-38	1500	38	<220	4 105*120	4.15	130x78x96	220x93x123	
DE-W55	40	50	N4105ZDS	1500	56	<210	4 105*120	4.15	153x78x115	230x93x123	
DE-W66	48	60	N4105ZDS	1500	56	<210	4 105*120	4.15	159x78x115	239x93x123	
DE-W74	54	68	N4105ZLDS	1500	66	<210	4 105*120	4.15	159x85x121	239x98x128	
DE-W96	70	88	R6105ZDS	1500	94	<220	6 105*125	6.49	186x90x121	285x108x160	
DE-W96	70	88	4RT55-88D	1500	88	<205	4 110*140	5.32	178x85x121	260x105x150	
DE-W110	80	100	R6105ZLDS	1500	100	<218	6 105*125	6.49	186x90x121	285x108x160	
DE-W110	80	100	4RT55-88D	1500	88	<205	4 110*140	5.32	186x90x121	280x105x150	
DE-W132	96	120	4RT55-110D	1500	110	<205	4 110*140	5.32	186x90x121	280x105x150	
DE-W138	100	125	R6105AZLDS	1500	121	<218	6 105*130	6.75	235x103x160	300x110x150	
DE-W165	120	150	R6105BZLDS	1500	132	<218	6 105*135	7.01	235x103x160	315x120x162	
DE-W165	120	150	6RT80-132D	1500	132	<205	6 110*140	7.98	235x103x160	315x120x162	
DE-W220	160	200	6RT80-176DE	1500	176	<205	6 110*140	7.98	273x105x172	340x130x185	
DE-W275	200	250	WT10B-231DE	1500	231	<205	6 126*130	10.09	279x105x172	380x130x200	
DE-W344	250	313	WT13B-308DE	1500	308	<205	6 131*155	12.53	279x105x172	400x135x210	
DE-W413	300	375	WT13B-330DE	1500	330	<205	6 131*155	12.53	279x105x172	400x135x210	
DE-W18	13	16	4YT23-20D	1800	22	<240	4 88*95	2.31	130x78x96	220x93x123	
DE-W25	18	23	N4100DS-30	1800	33	<225	4 100*115	3.61	130x78x96	220x93x123	
DE-W31	22	28	N4100DS-30	1800	33	<225	4 100*115	3.61	130x78x96	220x93x123	
DE-W37	27	33	N4100DS-30	1800	33	<220	4 100*115	3.61	130x78x96	220x93x123	
DE-W47	34	43	N4105DS-38	1800	41.8	<210	4 105*120	4.15	130x78x96	230x93x123	
DE-W55	40	50	N4100ZDS-42	1800	46.2	<210	4 105*120	4.15	130x78x96	239x93x123	
DE-W69	50	63	N4105ZDS	1800	61.6	<210	4 105*120	4.15	153x78x115	239x98x128	
DE-W83	60	75	N4105ZLDS	1800	72.6	<220	4 105*120	4.15	159x78x115	285x108x160	
DE-W91	66	83	4RT55-88D	1800	96.8	<205	4 110*140	5.32	159x85x121	260x108x150	
DE-W106	77	96	R6105ZDS	1800	92.4	<218	6 105*125	6.49	186x90x121	285x108x160	
DE-W110	80	100	4RT55-88D	1800	96.8	<205	4 110*140	5.32	178x85x121	280x105x150	
DE-W124	90	113	R6105ZLDS	1800	110	<205	6 105*125	6.49	186x90x121	290x105x150	
DE-W124	90	113	4RT55-110D	1800	121	<218	4 110*140	5.32	186x90x121	280x105x150	
DE-W138	100	125	4RT55-110D	1800	121	<218	4 110*140	5.32	186x90x121	280x105x150	
DE-W151	110	138	R6105AZLDS	1800	133.1	<205	6 105*130	6.75	235x103x160	315x120x162	
DE-W179	130	163	R6105BZLDS	1800	145.2	<205	6 105*135	7.01	235x103x160	315x120x162	
DE-W179	130	163	6RT80-132D	1800	145.2	<205	6 110*140	7.98	235x103x160	305x130x185	
DE-W220	160	200	6RT80-176DE	1800	193.6	<205	6 110*140	7.98	273x105x172	340x130x185	

. Why Choose Us:

Dedicated

We are DEDICATED to meet Customers' need.

Enthusiasm

We respond to our Customers' ENTHUSIASM

Loyalty

We cherish our Customers' LOYALTY

Luxury

We aim to establish our own LUXURY brand

Efficient

We offer our EFFICIENT service

Newest

We adopt NEWEST technologies for products

Trust

We strive for winning the TRUST from Customers

. QUALIFICATION CERTIFICATE:



. FACTORY INTERIOR:



- 1: The diesel generator should be placed in a well ventilated area to ensure heat dissipation;
- 2: Diesel generators should regularly inspect and replace vulnerable parts such as engine oil and air filter elements to ensure their normal operation;
- 3: Diesel generators should be avoided from being used in high-temperature environments to avoid affecting the performance of the diesel engine;
- 4: Diesel generators should be avoided in environments with high levels of dust to avoid affecting heat dissipation.





+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDECITY,FUJIAN.CHINA