

CHINA

DELLENT

DE-P275

CE/ISO9001

20-30 DAYS

bargain face-to-face

1 MONTH 600PCS

PLASTIC WRAP OR PLYWOOD CASE

200 Kw Perkins Diesel Generator Water Cooled 1000 Hours Warranty

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 PC
- Price:

Our Product Introduction

- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



Product Specification

- Name:
- Cooling Method:
- Fuel Type:
- Rated Frequency:
- Engine Brand:
- Speed:
- Warranty:
- Highlight:

200 Kw Perkins Diesel Generator

Water-Cooling System

Diesel

- Perkins 1500RPM/1800RPM

50HZ/60HZ

- 12 Months/1000 Hours
- 200 Kw Perkins Diesel Generator, Perkins Diesel Generator Water Cooled, 200kw Perkins Genset

CE Perkins Diesel Generator about 200kW.

Don't settle for less when it comes to your power needs. Choose aPerkins generator from our dealership today and experience the power and reliability that only Doosan can offer. Contact us to learn more about our Perkins generators and services. Perkins generator with international Warranty Service

. PRODUCT

5	0 60 z Hz	TE	CHN	ICA	L D/	ATA	-			the second second	Dies	el Gener	ator Set	
	Genset Perfomance						Engine Performance					Dimension(L+W+H)		
	Genset Model	Prim		Standb		Engine model	Speed	Prine	Fuel Cons. (100% Load)	Cylinder- Bore+Stroke	Displace		Silent Type	
								power kw	Lik	Otr-mm	-ment			
	DE-P10	7.2	9	8	10	403D-11G	1500	8.6	2.6	3L+77×81	1.131	115×74×99	180×84×110	
	DE-P14	10	12.5	11	14	403A-15G1	1500	12.2	3.7	3L-84×90	1,496	115×74×99	180×84×110	
	DE-P17	12	15	13.2	16.5	403A-15G2	1500	14	5	3L-84×90	1.496	115×74×99	180×84×110	
	DE-P22	16	20	17.6	22	404A-22G1	1500	18.7	5.3	4L-84×100	2.216	127×74×101	180×84×110	
	DE-P30	22	27.5	24	30	404D-22TG	1500	25.2	7.1	4L-84×100	2.216	136×74×101	180×84×110	
	DE-P33	24	30	26.4	33	1103A-33G	1500	28.2	7.2	3L-105×127	3.3	152×80×122	230×102×128	
	DE-P50 DE-P66	36 48	45 60	40	50 66	1103A-33TG1 1103A-33TG2	1500 1500	42.2 55	10.8 14.6	3L-105×127 3L-105×127	3.3 3.3	161×80×122 169×80×122	230×102×128 230×102×128	
	DE-P72	52	65	57.6	72	1104A-44TG1	1500	59.6	14.6	4L-105×127	4.4	181×80×124	240×102×128	
	DE-P88	64	80	70.4	88	1104A-44TG2	1500	73.4	18.7	4L-105×127	4.4	185×80×124	240×102×128	
	DE-P110	80	100	88	110	1104C-44TAG2	1500	93.6	22.6	4L-105×127	4.41	188×85×124	272×108×170	
	DE-P150	108	135	120	150	1106A-701G1	1500	122.7	30.2	6L-105×135	7.01	224×90×141	330×110×170	
	DE-P165	120	150	132	165	1106A-70TAG2	1500	136	33.4	6L-105×135	7.01	224×90×141	330×110×170	
	DE-P200	144	180	160	200	1106A-70TAG3	1500	163.9	41.6	6L-105+135	7.01	230×90×141	340×110×170	
	DE-P220	160	200	176	220	1106A-70TAG4	1500	178.9	45.8	6L-105×135	7.01	235×90×141	340×110×170	
1	DE-P250 DE-P275	200	225	200	250 275	1506A-E88TAG2 1506A-E88TAG3	1500	204	56	6L-112×149 6L-112×149	8.8 8.8	262×110×162 262×110×162	360=130×190 360×130×190	
5	DE-P275	220	275	240	300	1506A-E88TAG4	1500	244	60	6L-112×149 6L-112×149	8.8	273*110*162	380×130×190	
	DE-P330	240	300	264	330	1506A-E88TAG5	1500	267	65	6L-112×149	6.8	273×110×162	380×130×190	
	DE-P385	280	350	308	385	2206C-E13TAG2	1500	324	75	6L-130×157	12.5	299×120×185	420×140×223	
	DE-P450	320	400	360	450	2206C-E13TAG3	1500	368	85	6L-130×157	12,5	308×120×185	430×140×223	
	DE-P500	360	450	400	500	2506C-E15TAG1	1500	412	99	6L-137×171	15.2	345×120×198	470×160×223	
	DE-P550	400	500	440	550	2506C-E15TAG2	1500	451	106	6L-137×171	15.2	345×120×198	470×160×223	
	DE-P660	480	600	528	660	2806C-E18TAG1A	1500	532	129	6L-145×183	18.1	335×154×202	500×180×253	
	DE-P720	520 600	650 750	576	720 825	2806A-E18TAG2	1500	584 658	132	6L-145×183	18,1	341×154×202	500×180×253	
	DE-P825 DE-P880	640	800	660 704	825	4006-23TAG2A 4006-23TAG3A	1500 1500	705	157 172	6L-160×190 6L-160×190	22.921	402×171×221 402×171×221	580×200×253	
	DE-P1000	728	900	800	1000	4008TAG1A	1500	805	195	8L-160×190	30.561	470×205×235	680×228×258	
	DE-P1125	820	1025	900	1125	4008TA G2A	1500	899	215	8L-160×190	30.561	470×205×235	680×228×258	
	DE-P1375	1000	1250	1100	1375	4012-46TWG2A	1500	1113	259	12V-160×190	45.842	485×205×252		
	DE-P1650	1200	1500	1320	1650	4012-46TAG2A	1500	1331	310	12V-160×190	45.842	485×205×252	40 feet high container	
	DE-P1875	1360	1700	1500	1875	4012-46TAG3A	1500	1500	370	12V-160×190	45.842	497*205*252		
	DE-P2000	1480	1850	1600	2000	4016-61TRG1	1500	1648	371	16V-160×190	61.123	634×220×268	× 1	
	DE-P2200	1600	2000	1760	2200	4016-61TRG2	1500	1774	405	16V-160×190	61.123	624×220×268	1	
4	DE-P2500	Touu	2250	2000	2000	4016-61TRG3	1500	1975	470	16V-160×190	61,123	625×220×268	1 3.0	
	DE-P13	9	11.25	10	12.5	403D-11G	1800	10.7	3	3L-77×81	1.131	115×74×99	180×84×110	
	DE-P17	12	15	13.2	16.5	403D-15G	1600	14.7	4.27	3L-84×90	1.496	115×74×99	180×84×110	
	DE-P20	14.4	18	16	20	403A-15G2	1800	16	5	3L-84×90	1.496	115×74×99	180×84×110	
	DE-P28	20	25 30	22	27.5	404D-22G	1800	22 30 3	6.2	4L-84×100	2.216	127×74×101	180×84×110	
	DE-P33 DE-P39	24	30	26.4 30.8	38.5	404D-22TG 1103A-33G	1800	30.3	8.3 8.6	4L-84×100 3L-105×127	2.216	136×74×101 152×80×122	180×84×1100 230×102×128	
	DE-P60	43	54	48	60	1103A-33TG1	1800	50.5	12.9	3L-105×127	3.3	161×80×122	230×102×128	
	DE-P75	54	67.5	60	75	1103A-33TG2	1800	63.3	16.6	3L-105×127	3.3	169×80×122	230×102×128	
	DE-P83	60	75	66	82.5	1104A-44TG1	1800	70.7	17.7	4L-105×127	4.4	181×80×124	240×102×128	
	DE-P103	75	93.75	82.5	103	1104A-44TG2	1800	84.5	22.3	4L-105×127	4,4	185×80×124	240×102×128	
	DE-P125	90	112.5	100	125	1104C-44TAG2	1800	106.8	26.9	4L-105×127	4.41	188×85×124	272×108×170	
ZHDS	DE-P165 DE-P188	120	150	132	165	1106A-70TG1	1800	140.5	35.2	8L-105×135	7.01	224×90×141	330×110×170	
	DE-P188 DE-P220	135	169 200	150	187.5	1106A-70TAG2 1106A-70TAG3	1800	155 180.5	38.2 46.4	6L-105×135 6L-105×135	7.01	224×90×141 230×90×141	330×110×170 340×110×170	
	DE-P220 DE-P270	190	245	216	270	1506A-E88TAG2	1800	218	46.4 56	6L-100×130 6L-112×149	8.8	262×110×162	360×110×170	
	DE-P310	225	281	248	310	1506A-E88TAG3	1800	250	63	6L-112×149	B.8	262×110×162	360×130×190	
	DE-P385	280	350	308	385	1506A-E88TAG5	1600	300	77	6L-112×149	8.8	273×110×162	380×130×190	
	DE-P440	320	400	352	440	2206A-E13TAG2	1800	373	81	6L-13D×157	12,5	299×120×185	420×140×223	
	DE-P550	400	500	440	550	2506C-E157AG1	1800	453	106	6L-137×171	15.2	345×120×198	470×160×223	
	DE-P688	500	625	550	687.5	2806C-E18TAG1A	1800	568	130	6L+145×183	18,1	335×154×202	500×180×253	
	DE-P825	600	750	660	825	4006-23TAG2A	1800	684	177	6L-160×190	22.921	402×171×221	580×200×253	
	DE-P935 DE-P1100	680 800	850	748	935 1100	4006-23TAG3A 4008TAG2	1800 1800	759 898	200 224	6L-160×190 8L-160×190	22.921	402×171×221 470×205×235	580×200×253 680×228×258	
	DE-P1100	1000	1250	1100	1375	4012-46TWG2A	1800	1113	266	12V-160×190	45.842	485*205*252	000*220*20t	
	DE-P1650	1200	1500	1320	1650	4012-46TAG2A	1800	1332	319	12V-160×190	45.842	485×205×252	40 feet high	
		1360		1500		4012-46TAG3A	1800	1500	361	12V-160+190		497*205×252	container	

. Why Choose Us:





LOYALTY We cherish our Customers' LOYALTY

We aim to establish our own LUXURY brand

Efficient We offer our EFFICIENT service

CONTRACTOR We adopt NEWEST technologies for products



We strive for winning the TRUST from Customers

. QUALIFICATION CENTIFICATE:



FAQ

- Q: What's your delivery time?
- A: Standard product 20 days 30 days.
- Q: Can we add our logo to products?

A: Yes, there are several ways to do this. We can put the label of your logo on the products or make the silk print of your logo on the products. It is free.

Q: Can we customize the product?

A: We have a very experienced technical team, we can customize any product according to your requirements, such as synchronization system, wet exhaust system, ultra-silent system

	Fuan Dellent Electric & Machinery Co., Ltd.							
٥	+8613706938606	jennifer@dellent.com	e dellentpower.com					
Ν		NDUSTRIAL AREA CHENG IINGDECITY,FUJIAN.CHIN/						

a.