

CHINA DELLENT

CE/ISO9001

20-30 DAYS

bargain face-to-face

1 MONTH 600PCS

PLASTIC WRAP OR PLYWOOD CASE

DE-P825

Water Cooled 600 Kw Perkins Generator Set DE-P825 12 Months Warranty

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 PC
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



Product Specification

- Name:
- Engine Brand:
- Cooling Method:
- Fuel Type:
- Rated Frequency:
- Speed:
- Warranty:
- Highlight:
- Perkins Water-Cooling System

600 Kw Perkins Generator

- Diesel
- uency: 50HZ/60HZ
 - 1500RPM/1800RPM
 - 12 Months/1000 Hours
 - Water Cooled 600 Kw Perkins Generator, 600 Kw Perkins Generator Set, 600kw Water Cooled Generator Set

CE Perkins Diesel Generator about 600kW

Looking for reliable **Perkins** generators for your power needs? Look no further than our**Perkins** generator dealership! We are proud to offer a wide range of high-quality **Perkins** gensets that are perfect for both residential and commercial use. Don't settle for less when it comes to your power needs. Choose a**Perkins** generator from our dealership today and experience the power and reliability that only **Perkins** can offer. Contact us to learn more about our**Perkins** generators and services. **Perkins** generator with international Warranty Service

							WATER-COOLED Series				Dimension(L+W+H)		
		Prime Power		Standby Power				Prime	Fuel Cons.	Cylinder-	Displace		
								power	(100% Load)	Bore*Stroke	-ment		
		kW .	kVA .	kW	kVA		1000	kW	Lth	Qtymm	18.	ûm.	cm -
	DE-P10	7.2	9	8	10	403D-11G	1500	8.6	2.6	3L-77×81	1.131	115×74×99	180×84×110
	DE-P14	10	12.5	11	14	403A-15G1	1500	12.2	3.7	3L-84×90	1,496	115×74×99	180×84×110
	DE-P17 DE-P22	12	15 20	13.2 17.6	16.5	403A-15G2 404A-22G1	1500	14 18.7	5	3L-84×90 4L-84×100	1.496	115×74×99 127×74×101	180×84×110 180×84×110
	DE-P30	22	27.5	24	30	404D-22TG	1500	25.2	7.1	4L-84×100	2.216	136×74×101	180×84×110
	DE-P33	24	30	26.4	33	1103A-33G	1500	28.2	7.2	3L-105×127	3.3	152×80×122	230×102×128
	DE-P50	36	45	40	50	1103A-33TG1	1500	42.2	10.8	3L-105×127	3.3	161×80×122	230×102×128
	DE-P66	48	60	52.8	66	1103A-33TG2	1500	55	14.6	3L-105×127	3.3	169×80×122	230×102×128
	DE-P72	52	65	57.B	72	1104A-44TG1	1500	59.6	14.6	4L-105×127	4.4	181×80×124	240×102×128
	DE-P88	64	80	70.4	88	1104A-44TG2	1500	73.4	18.7	4L-105×127	4.4	185×80×124	240×102×128
	DE-P110 DE-P150	80	100	88 120	110	1104C-44TAG2 1106A-70TG1	1500 1500	93.6 122.7	22.6 30.2	4L-105×127 6L-105×135	4.41	188×86×124 224×90×141	272×108×170 330×110×170
	DE-P165	120	150	132	165	1106A-70TAG2	1500	136	33.4	6L-105×135	7.01	224×90×141	330×110×170
	DE-P200	144	180	160	200	1106A-70TAG3	1500	163.9	41.6	6L-105×135	7.01	230×90×141	340×110×170
	DE-P220	160	200	176	220	1106A-70TAG4	1500	178.9	45.8	6L-105×135	7.01	235×90×141	340×110×170
	DE-P250	180	225	200	250	1506A-E88TAG2	1500	204	51	6L-112×149	8.8	262×110×162	360=130×190
1	DE-P275	200	250	220	275	1506A-E88TAG3	1500	222	56	6L+112×149	B.8	262×110×162	360×130×190
21	DE-P300	220	275	240	300	1506A-E88TAG4	1500	244	60	6L-112×149	8.8	273*110*162	380×130×190
	DE-P330	240	300	264	330	1506A-E88TAG5	1500	267	65	6L-112×149	B.8	273×110×162	380×130×190
	DE-P385	280	350	308	385	2206C-E13TAG2	1500	324	75	6L-130×157	12.5	299×120×185	420×140×223
	DE-P450 DE-P500	320	400	360	450	2206C-E13TAG3 2506C-E15TAG1	1500	412	99	6L-130×157 6L-137×171	12,5	308×120×185 345×120×198	430×140×223 470×160×223
	DE-P550	400	500	440	550	2506C-E15TAG2	1500	412	106	6L-137×171	15.2	345×120×198	470×160×223
	DE-P660	480	600	528	660	2806C-E18TAG1A	1500	532	129	6L-145×183	18.1	335×154×202	500×180×253
	DE-P720	520	650	576	720	2806A-E18TAG2	1500	584	132	6L-145×183	18.1	341×154×202	500×180×253
	DE-P825	600	750	660	825	4006-23TAG2A	1500	658	157	6L-160×190	22.921	402×171×221	580×200×253
	DE-P880	640	800	704	880	4005-23TAG3A	1500	705	172	6L-160×190	22.921	402×171×221	580×200×253
	DE-P1000	728	900	800	1000	400BTAG1A	1500	805	195	8L-160×190	30.561	470×205×235	680×228×256
	DE-P1125	820	1025	900	1125	4008TAG2A	1500	899	215	8L-160×190	30.561	470×205×235	680×228×256
	DE-P1375 DE-P1650	1000	1250	1100	1375	4012-46TWG2A 4012-46TAG2A	1500	1113	259 310	12V-160×190	45.842	485×205×252 485×205×252	40 feet high
	DE-P1875	1360	1700	1500	1875	4012-46TAG3A	1500	1500	370	12V-160×190	45.842	497*205*252	container
	DE-P2000	1480	1850	1600	2000	4016-61TRG1	1500	1648	371	16V-160×190	61.123	634×220×268	
	DE-P2200	1600	2000	1760	2200	4016-61TRG2	1500	1774	405	16V-160×190	61.123	624×220×268	5
	DE-P2500	1800	2250	2000	2500	4016-61TRG3	1500	1975	470	16V-160×190	61.123	625×220×268	1.1.1
1	DE-P13	9	11.25	10	12.5	403D-11G	1800	10.7	3	3L-77×81	1.131	115×74×99	180×84×110
	DE-P13 DE-P17	12	11.25	13.2	12.5	403D-11G 403D-15G	1800	10.7	4.27	3L-77×81 3L-84×90	1.131	115×74×99	180×84×110 180×84×110
	DE-P20	14.4	18	16	20	403A-15G2	1800	16	5	3L-84×90	1.496	115×74×99	180×84×110
	DE-P28	20	25	22	27.5	404D-22G	1800	22	6.2	4L-84×100	2.216	127×74×101	180×84×110
	DE-P33	24	30	26.4	33	404D-22TG	1800	30.3	8.3	4L-84×100	2,216	136×74×101	180+84+1100
	DE-P39	28	35	30.8	38.5	1103A-33G	1800	33.2	8.6	3L-105×127	3.3	152×80×122	230×102×128
	DE-P60	43	54	48	60	1103A-33TG1	1800	50.5	12.9	3L-105×127	3.3	161×80×122	230×102×128
	DE-P75	54	67.5	60	75	1103A-33TG2	1800	63.3	16.6	3L-105×127	3.3	169×80×122	230×102×128
	DE-P83 DE-P103	60 75	75 93.75	66 82.5	82.5	1104A-44TG1 1104A-44TG2	1800	70.7	17.7	4L-105×127 4L-105×127	4.4	181×80×124 185×80×124	240 × 102 × 128 240 × 102 × 128
	DE-P103	90	112.5	100	103	1104C-44TAG2	1800	106.8	26.9	4L-105×127 4L-105×127	4.41	188×85×124	240×102×128 272×108×170
	DE-P165	120	150	132	165	1106A-70TG1	1800	140.5	35.2	8L-105×135	7.01	224×90×141	330×110×170
	DE-P188	135	169	150	187.5	1106A-70TAG2	1600	155	38.2	6L-105×135	7.01	224×90×141	330×110×170
	DE-P220	160	200	176	220	1106A-70TAG3	1800	180.5	46.4	6L-105×135	7.01	230×90×141	340×110×170
	DE-P270	196	245	216	270	1506A-E88TAG2	1800	218	56	6L-112×149	8.8	262×110×162	360×130×190
	DE-P310	225	281	248	310	1506A-E88TAG3	1800	250	63	6L+112×149	B.8	262×110×162	360×130×190
	DE-P385	280	350	308	385	1506A-E88TAG5	1600	300 373	77 81	6L-112×149	8.8	273×110×162	380×130×190
	DE-P440 DE-P550	320	400	352	440 550	2206A-E13TAG2 2506C-E15TAG1	1800	373	81	6L-130×157 6L-137×171	12.5	299×120×185 345×120=198	420×140×223 470×160×223
	DE-P688	500	625	550	687.5	2806C-E15TAG1A	1800	403	130	6L-137×171 6L-145×183	18.1	335×154×202	470×160×223 500×180×253
	DE-P825	600	750	660	825	4006-23TAG2A	1800	684	177	6L-160×190	22.921	402×171×221	580×200×253
	DE-P935	680	850	748	935	4006-23TAG3A	1800	759	200	6L-160×190	22.921	402×171×221	580×200×253
	DE-P1100	800	1000	880	1100	4008TA G2	1800	898	224	8L-160×190	30.561	470×205×235	680×228×258
	DE-P1375	1000	1250	1100	1375	4012-46TW/G2A	1800	1113	266	12V-160+190	45.842	485×205×252	in territoria
	DE-P1650	1200	1500	1320	1650	4012-46TAG2A	1800	1332	319	12V-160×190	45.842	485×205×252	40 feet high container
	DE-P1875	1360	1700	1500	1875	4012-46TAG3A	1800	1500	361	12V-160+190	45 842	497×205×252	and the second s

. Why Choose Us:





LOYALTY We cherish our Customers' LOYALTY

We aim to establish our own LUXURY brand

Efficient We offer our EFFICIENT service

We adopt NEWEST technologies for products



We strive for winning the TRUST from Customers

. QUALIFICATION CENTIFICATE:





Fuan Dellent Electric & Machinery Co., Ltd.

C +8613706938606 Signal jennifer@dellent.com

ellentpower.com

NO.7, JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY, NINGDECITY, FUJIAN.CHINA